



recommends the following fasteners,

<u>HIDfast fasteners</u>	<u>HF3</u>	<u>HF3M</u>	<u>HF3W</u>	<u>HF2.75TG</u>	<u>EF2.25SS</u>	<u>EF2.25EC</u>
Decking Thickness	2x or less	2x or less	2x or less	5/4	5/4" or less	5/4" or less
Spacer bar (gap)	1/8"	3/16"	¼"	N/A	0, to ¼"	0, to ¼"
Fastener length	3"	3"	3"	2 ¾"	2.25"	2.25"
AZEK square edge	YES	YES	YES		YES	YES
AZEK grooved edge	YES	YES	YES			
Square edge PVC	YES	YES	YES		YES	YES
Grooved PVC	YES	YES	YES			
Pressure Treated 5/4 x6	x	x	x		YES – 0 gap	YES - 0
Pressure Treated 5/4 x6 KD	x				YES – 1/8 +	YES – 1/8+
Pressure Treated 2x6 KD	YES	x	x		x	x
Cedar, Redwood and similar	YES	YES	YES		YES	YES
Mahogany 1x4 (medium density)	YES	YES	YES		Yes-1/8 - ¼"	YES 1/8-¼"
"    1x6		YES	YES		YES – ¼"	YES – ¼"
Mahogany 5/4" x4 (medium D.)		YES	YES		YES	YES
Mahogany 5/4" x6 (medium D.)		YES	YES		YES – ¼"	YES – ¼"
Mahogany " x4 (hard-grooved only))	YES	YES	YES		x	x
Mahogany " x6 (hard-grooved only))		YES	YES		x	x
Timbertech – grooved only		YES	YES		x	x
Trex – grooved only			YES		YES	x
Fiberon – WPC –grooved only		YES	YES		x	x
Evergrain – grooved only		YES	YES		x	x
Moisture Shield – grooved only		YES	YES		x	x
All WPC Composites – grooved only		YES	YES		x	x
T&G - AZEK or PVC				YES	YES-*.250 gap	YES-.250
1x4 & *5/4 x 4 - Fir, Syp					YES- .150	YES - .150
Aretis - T&G					YES- .150	YES- .150
Koma – T&G					YES- .150	YES- .150